




SUPER LINK

Deck Space: 18 Meter (Front 6m, Back 12m)
 Width: 2.5m - 2.9m
 Average Tile Load: 7200
 Loading Capacity: 34 Ton



TRI-AXLE

Deck Space: 14 Meter
 Width: 2.5m - 2.9m
 Average Tile Load: 6000
 Loading Capacity: 28 Ton



TRI-AXLE CRANE TRUCK

Deck Space: 14 Meter
 Width: 2.5m - 2.9m
 Average Tile Load: 5800
 Loading Capacity: 28 Ton



14 TON RIGID

Deck Space: 7 Meter
 Width: 2.5m - 2.9m
 Average Tile Load: 3300
 Loading Capacity: 14 Ton



10 TON RIGIT (Double Back Axle)

Deck Space: 6 Meter
 Width: 2.5m - 2.9m
 Average Tile Load: 2200
 Loading Capacity: 10 Ton



8 TON RIGID (Single Back Axle)

Deck Space: 6 Meter
 Width: 2.5m - 2.9m
 Average Tile Load: 1500
 Loading Capacity: 8 Ton

Marley Roofing's guide to Vehicle Configurations

All transportation vehicles must be capable of being driven within an area contained between concentric circles with radii of 12.50 meters and 5.30 meters, so that no part of the vehicle/ combination vehicle projects outside the contained area between these two circles.

